

The maintenance schedule given below describes the maintenance requirements for the Daytona 675.

**⚠ Warning**

The importance of good maintenance cannot be overestimated. The tasks described will help to ensure the safe and reliable operation of the Triumph motorcycle. Never attempt to cut costs by neglecting the maintenance requirements of your machine as this will result in the premature failure of the component(s) concerned and may lead to an unsafe riding condition and an accident.

**Scheduled Maintenance Chart**

<b>Operation Description</b>	Odometer Reading in Miles (Kms) or time period, whichever comes first.						
	Every	500 (800) 1 month	6000 (10000) 1 year	12000 (20000) 2 years	18000 (30000) 3 years	24000 (40000) 4 years	30000 (50000) 5 years
Engine/oil cooler - check for leaks	Day	•	•	•	•	•	•
Engine oil - renew	-	•	•	•	•	•	•
Engine oil filter - renew	-	•	•	•	•	•	•
Valve clearances - check	-			•		•	
Air cleaner - renew	-			•		•	
Engine ECM - check for stored DTC's	-	•	•	•	•	•	•
Spark plugs - check	-		•		•		•
Spark plugs - renew	-			•		•	
Throttle bodies - balance	-		•	•	•	•	•
Throttle cable - check/adjust	Day	•	•	•	•	•	•
Coolant level - check/adjust	Day	•	•	•	•	•	•
Coolant - renew	-			•		•	
Cooling system - check for leaks	Day	•	•	•	•	•	•
Fuel system - check for leaks	Day	•	•	•	•	•	•
Lights, instruments & electrical systems - check	Day	•	•	•	•	•	•
Steering - check for free operation	Day	•	•	•	•	•	•
Headstock bearing - check/adjust	-		•	•	•	•	•
Headstock bearing - lubricate	-			•		•	
Forks - check for leaks/smooth operation	Day	•	•	•	•	•	•
Fork oil - renew	-					•	
Brake fluid levels - check	Day	•	•	•	•	•	•
Brake fluid - renew	-			•		•	
Brake pads - check wear levels	Day	•	•	•	•	•	•

Scheduled Maintenance Chart - Daytona 675 continued.

Operation Description	Odometer Reading in Miles (Kms) or time period, whichever comes first.						
	Every	500 (800) 1 month	6000 (10000) 1 year	12000 (20000) 2 years	18000 (30000) 3 years	24000 (40000) 4 years	30000 (50000) 5 years
Brake callipers - check for leaks/ seized pistons	Day	•	•	•	•	•	•
Brake master cylinder - check for leaks	Day	•	•	•	•	•	•
Drive chain - lubricate	Every 200 miles (300 Kms)						
Drive chain wear check	Every 500 miles (800 Kms)						
Drive chain rubbing strip - check	-		•	•	•	•	•
Drive chain slack - check/adjust	Day	•	•	•	•	•	•
Fasteners - inspect visually for security	Day	•	•	•	•	•	•
Wheels - inspect for damage	Day	•	•	•	•	•	•
Tyre wear/tyre damage - check	Day	•	•	•	•	•	•
Tyre pressures - check/adjust	Day	•	•	•	•	•	•
Clutch cable - check/adjust	Day	•	•	•	•	•	•
Stand - check operation	Day	•	•	•	•	•	•
Exhaust butterfly valve cables - check/adjust					•		
Secondary exhaust clamp bolts - check/adjust	-	•	•	•	•	•	•
Secondary air injection system - check	-			•		•	
Fuel/evaporative* hoses - renew	-					•	

\* Evaporative hoses fitted to California models only